


**SERIES SKI AC CAPACITIVE LEVEL SENSORS**


- Wide variety of sizes
- Various body materials
- 44 - 250v AC
- Protected to IP 67

**GENERAL SPECIFICATIONS**

SN	Size	Housing Material	Max Frequency	Temp Drift Hysteresis	O/P	Part No.
2-15mm		A. PVC B. PVC C. PA	25HZ	$\leq 15\%$ of SN $\leq 10\%$ of SN	N/O	SK115M18ACNBSY ART.07513
					N/C	SK115M18ACNBOY ART.07514
2-15mm		A. PTFE B. ms/cr C. Pom	25HZ	$\leq 15\%$ of SN $\leq 10\%$ of SN	N/O	SK115M18ACNBSMS ART.07503
					N/C	SK115M18ACNBOMS ART.07504
2-15mm		A. PTFE B. PTFE C. PTFE	25HZ	$\leq 15\%$ of SN $\leq 10\%$ of SN	N/O	SK115M18ACNBSPFTE ART.07505
					N/C	SK115M18ACNBOPTFE ART.07506
2-25mm		A. PTFE B. ms/cr C. Pom	25HZ	$\leq 10\%$ of SN $\leq 10\%$ of SN	N/O	SK125M30ACNBSMS ART.07509
					N/C	SK125M30ACNBOMS ART.07510
2-25mm		A. PTFE B. PTFE C. PTFE	25HZ	$\leq 10\%$ of SN $\leq 10\%$ of SN	N/O	SK125M30ACNBSPTFE ART.07511
					N/C	SK125M30ACNBOPTFE ART.07512

OTHER OPTIONS AVAILABLE

**Please note.**

Level sensors of the SK1-AC series can **also** be supplied in the **M32x1.5 housing**.  
 The technical data are the same as for the devices in the M30x1,5 housing.